

## PAK-412 - Active Speaker Cabinet



### PAK-400 serien

PAK-400 serien er velegnet til mange formål, udnytter moderne teknologi og en individuel lydindstilling, som opfylder flere forskellige behov. Forstærkersystemet er en kombination af class D til bassen og class A/B til hornet. Ved brug af presets er det nemt at finde den perfekte lyd og med high-pass filtret, der aktiveres ved 75 Hz, kan højttalerne nemt matches med subwooferen PSUB-418AK. **Aktivt PA højttalersystem med 2-kanals forstærker, 700 W**

- Kompakt 2-vejs full range system med robust plastikkabinet
- Moderne forstærkersystem (bas: class D, horn: class A/B)
- Lydtryk ved nominel effekt: 124 dB
- 4 presets: normal, Hi-Fi, DJ og voice, high-pass filter: 75 Hz
- MIC/LINE indgang
- LED indikator for power, signal og peak/clipping
- M10 gevindindsats (2 i toppen, 2 i bunden og 1 på bagsiden)
- Grundet kabinettets form også egnet som scenemonitor
- Flange til placering på stativ og bærehåndtag

### TASTENWELT 06/2015

"The PAK-400 series from IMG Stage Line features individual adjustment facilities using modern technology which makes it suitable for most versatile applications; definitely a concept that works: this series provides a perfect system for everyone, including keyboard entertainers, combinations of entertaining music and DJs."

## Technical data:

active	: 1
Active/passive	: active
Transmission technology	: cable
Total output power	: 700 W
Power rating (RMS)	: 450Â (350+100)Â W
Total power rating	: -
Power rating (RMS)	: -
Impedance	: -
Frequency range	: 40-20,000 Hz
THD	: -
S/N ratio	: -
Input signal	: 260 mV/10 kOhm (line), 2 mv/10 kOhm (mic)
System	: 12/2 full range
Full range speaker	: -
Bass speaker	: 30 cm (12") bass speaker
Midrange speaker	: -
Tweeter	: 33 mm (1.3") tweeter
Number of speakers	: 2
Speaker size	: 30 cm (12")
SPL	: 98 dB/W/m
Max. rated SPL	: 124 dB
Radiation angle/beam angle	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Features	: -
Housing material	: plastic
Colour	: black
Mounting device	: M10 threaded inserts, stand sleeve
Protected against ball rebound	: -
Protection class	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: &acd; 230Â V/50Â Hz/500Â VA
Dimensions	: 405 x 670 x 340Â mm
Width	: 405 mm
Height	: 670 mm

Depth	: 340 mm
Weight	: 17.3 kg
Inputs	: 1 x comb. XLR/6.3 mm (line/mic)
Outputs	: 1 x XLR, par. out
Replacement voice coil	: -
Other features	: 4 selectable presets switchable high-pass filter: 75 Hz
Accessories	: -
Packing dimensions (W x H x L)	: 0.43 x 0.76 x 0.49 m
Gross weight	: 19.69 kg
Net weight	: 17.57 kg