
-

Technical data:

Low-impedance	: 1
Active/passive	: passive
Transmission technology	: cable
Total output power	: -
Power rating (RMS)	: -
Total power rating	: 600 W
Power rating (RMS)	: 300 W
Impedance	: 8 Ohm
Frequency range	: 45-18,500 Hz
THD	: -
S/N ratio	: -
Input signal	: -
System	: 2-way bass-reflex
Full range speaker	: -
Bass speaker	: 38Â cm (15")
Midrange speaker	: -
Tweeter	: dyn. mid-high rangehorn speaker
Number of speakers	: 2
Speaker size	: 38Â cm (15")
SPL	: 102 dB/W/m
Max. rated SPL	: 126 dB
Radiation angle/beam angle	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Features	: -
Housing material	: plastic
Colour	: black
Mounting device	: M8 threaded inserts, stand sleeve
Protected against ball rebound	: -
Protection class	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: -
Dimensions	: 450 x 670 x 345Â mm
Width	: 450 mm
Height	: 670 mm

Depth	: 345 mm
Weight	: 23 kg
Inputs	: 1 x NEUTRIK SPEAKON
Outputs	: 1 x NEUTRIK SPEAKONpar. out
Replacement voice coil	: -
Other features	: -
Accessories	: PAB-515BAG
Packing dimensions (W x H x L)	: 0.53 x 0.75 x 0.42 m
Gross weight	: 29.7 kg
Net weight	: 24.48 kg