

ETS-530TW/WS - PA Speaker Column



PA søjlehøjtalere

- 100 V line-teknologi eller 8 Ohm drift
- 2-vejs version (med ekstra indbygget tweeter, som giver en klart bedre lyd)
- Integreret delefilter
- 6-trins effektomskifter
- 2 x 6 mm gevindbøsning
- Plastikkabinet og frontgitter i metal i sort (SW) eller hvid (WS)
- Monteringsbeslag medfølger
- Tilslutning via klemterminaler

Technical data:

100 V	: 1
Low-impedance	: 1
Active/passive	: passive
Transmission technology	: 100 V
Total output power	: -
Power rating (RMS)	: -
Total power rating	: 60 W
Power rating (RMS)	: 30/15/7.5/4/2 W (100 V) 30 W (8 Ohm)
Impedance	: 8 Ohm
Frequency range	: 85-20,000 Hz
THD	: -
S/N ratio	: -
Input signal	: -
System	: 2-way
Full range speaker	: -
Bass speaker	: -
Midrange speaker	: -
Tweeter	: -
Number of speakers	: 4+1
Speaker size	: -
SPL	: 89 dB/W/m
Max. rated SPL	: -
Radiation angle/beam angle	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Features	: -
Housing material	: plastic
Colour	: white
Mounting device	: mounting brackets
Protected against ball rebound	: -
Protection class	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: -
Dimensions	: 128 x 620 x 140 mm
Width	: 128 mm

Height	: 620 mm
Depth	: 140 mm
Weight	: 4.5 kg
Inputs	: -
Outputs	: -
Replacement voice coil	: -
Other features	: -
Accessories	: -
Packing dimensions (W x H x L)	: 0.18 x 0.18 x 0.73 m
Gross weight	: 4.94 kg
Net weight	: 4.56 kg