

## ETS-442TW/WS - PA Speaker Column



Weatherproof PA column speakers,  
with a top-quality sound.

- Weatherproof and hose-proof, extruded aluminium cabinet
- 100 V line technique
- 2-way version (with additional integrated tweeter for a clearly improved sound)
- Integrated crossover network
- Aluminium front grille
- Supplied with a robust tiltable and movable aluminium wall bracket
- Connection via cable with 4 power taps

## Technical data:

|                                |                        |
|--------------------------------|------------------------|
| Outdoors                       | : 1                    |
| weatherproof                   | : 1                    |
| 100 V                          | : 1                    |
| Active/passive                 | : passive              |
| Transmission technology        | : 100 V                |
| Total output power             | : -                    |
| Power rating (RMS)             | : -                    |
| Total power rating             | : -                    |
| Power rating (RMS)             | : 40/20/10/5 W         |
| Impedance                      | : -                    |
| Frequency range                | : 110-20,000 Hz        |
| THD                            | : -                    |
| S/N ratio                      | : -                    |
| Input signal                   | : -                    |
| System                         | : -                    |
| Full range speaker             | : -                    |
| Bass speaker                   | : -                    |
| Midrange speaker               | : -                    |
| Tweeter                        | : -                    |
| Number of speakers             | : 8+1                  |
| Speaker size                   | : -                    |
| SPL                            | : 93 dB/W/m            |
| Max. rated SPL                 | : -                    |
| Radiation angle/beam angle     | : -                    |
| Radiation angle, horizontal    | : -                    |
| Radiation angle, vertical      | : -                    |
| Features                       | : -                    |
| Housing material               | : aluminium            |
| Colour                         | : white                |
| Mounting device                | : wall bracket         |
| Protected against ball rebound | : -                    |
| Protection class               | : IP66                 |
| Admiss. ambient temp.          | : -20 °C to +50 °C     |
| Power supply                   | : -                    |
| Dimensions                     | : 124 x 1,016 x 108 mm |



|                                |                          |
|--------------------------------|--------------------------|
| Width                          | : 124 mm                 |
| Height                         | : 1,016 mm               |
| Depth                          | : 108 mm                 |
| Weight                         | : 6.9 kg                 |
| Inputs                         | : -                      |
| Outputs                        | : -                      |
| Replacement voice coil         | : -                      |
| Other features                 | : -                      |
| Accessories                    | : -                      |
| Packing dimensions (W x H x L) | : 0.165 x 0.195 x 1.12 m |
| Gross weight                   | : 7.89 kg                |
| Net weight                     | : 6.96 kg                |