

# PS-320/24S - Built-in Power Supply



Built-in power supply, 24 V

- Output current: 13.4 A (320 W)
- Protected against short circuit, overload and overvoltage
- Fine adjustment of output voltage
- Aluminium housing
- Mains connection and low-voltage connection via screw terminals

## Technical data:

|                             |                         |
|-----------------------------|-------------------------|
| Category                    | : built-in power supply |
| Input voltage               | : $\approx$ 100-240 V   |
| Output voltage              | : DC 24 V               |
| Output current              | : 13.4 A                |
| Charging time               | : -                     |
| Trickle charge              | : -                     |
| Polarity selection          | : -                     |
| Switchable output voltage   | : -                     |
| Reactivation                | : -                     |
| Connections                 | : screw terminals       |
| Cable length                | : -                     |
| Short-circuit protection    | : yes                   |
| Overload protection         | : yes                   |
| Overheat protection         | : yes                   |
| Reverse polarity protection | : -                     |
| Detection of faulty battery | : -                     |
| Protective class            | : -                     |
| Admiss. ambient temp.       | : -30-+70 °C            |
| Dimensions                  | : 115 x 30 x 215 mm     |
| Weight                      | : 0.824 kg              |
| Position                    | : -                     |
| Other features              | : -                     |