PA-302 - PA Amplifier



Mono PA mixing amplifier,
14 W.

- 1 microphone input and 1 line input, adjustable
- 2 speaker outputs, switchable
- Built-in speaker
- Can also be operated as an intercom system
- Supplied with hand-held push-to-talk microphone
- Siren and fog horn, automatic fog horn
- Metal housing
- Supplied with mounting brackets
- 12/24 V battery operation, automatic switching

Technical data:

Low-impedance	: 1
Peak output power	: 20 W
Power rating	: 14 W
Power rating at 2 Ohm	: -
Power rating at 4 Ohm	: -
Power rating at 8 Ohm	: -
Power rating at 16 Ohm	: -
Power rating at 100 V	: -
Power rating with 4 Ohm bridged operation	: -
Power rating with 8 Ohm bridged operation	: -
Output impedance	: -
Channels	: 2
Zones	: -
Inputs	: 3Â mV (mic), 50 mV (line)
Attenuation factor	: -
Frequency range	: 20-20,000 Hz
Crossover network	: -
Crossover frequency	: -
Integrated limiter	: -
Equalizer bass	: -
Equalizer midrange	: -
Equalizer treble	: -
S/N ratio	: 65 dB
Crosstalk attenuation	: -
THD	: < 0.5%
Phantom power	: -
Mains voltage	: -
Mains frequency	: -
Power consumption, operation	: -
Power consumption, standby	: -
Standby current	: -
Operating voltage (possible alternative)	: -
Power supply (possible alternative)	: -
Admiss. ambient temp.	: 0-40 °C

Width	: 175 mm

Height	:	60 mm
Depth	:	170 mm
Rack units, RU	:	-
Weight	:	1.4 kg
Connections	:	1 x 6.3Â mm jack (mic input), 1 x RCA (line input), 2 x 2-pole plug-in screw terminal (speakers), 1 x 3-pole plug-in screw terminal with jumper (external speakers)

Packing dimensions (W x H x L)	:	0.23 x 0.1 x 0.3 m
Gross weight	:	1.84 kg
Net weight	:	1.41 kg