

ECM-306B/SW - Boundary Microphone



Boundary microphone

- On/off switch with power LED
- Low cut and 10 dB attenuation, switchable
- Integrated electronics for direct connection to a phantom power supply DC 17-48 V
- Electronically balanced AF output
- 6 m connection cable with 3-pole mini XLR/XLR
- Supplied in a foam-padded plastic case

Especially suitable for the use as a desktop microphone!

Technical data:

Description	: boundary microphone
Version	: -
Transmission method	: cable
Polar pattern	: semi-supercardioid
System	: electret
Carrier frequency range	: -
Transmitting power	: -
Power supply	: -
Operating time	: -
Audio frequency range	: 30-20,000 Hz
Nominal impedance	: 250 Ohm
Sensitivity	: 22 mV/Pa
S/N ratio	: -
Max. sound pressure	: 130 dB
Power supply	: DC 17-48 V, phantom power
Gooseneck length	: -
Housing material	: -
Admiss. ambient temp.	: 0-40 °C
Dimensions	: 90 x 25 x 90 mm
Weight	: 200 g
Cable	: 6 m
Connection	: 3-pole mini XLR/XLR
Packing dimensions (W x H x L)	: 0.16 x 0.085 x 0.28 m
Gross weight	: 0.66 kg
Net weight	: 0.66 kg