

## TXS-1800HSE - Microphone Transmitter



Multifrequency pocket transmitter, 1.8 GHz,  
with UHF PLL technology.

- Suitable for combination with headband microphone or earband microphone with 3-pole mini XLR connector
- 192 selectable UHF frequencies (1,785-1,800 MHz) in 16 groups with 12 channels each, can be synchronised with receiver TXS-1800 via ADL function
- Adjustable sensitivity (0 dB, -3 dB, -6 dB)
- LCD for indicating frequency, gain setting and battery status
- Transmitting power: 10 mW (EIRP)
- Mute function
- Belt clip
- Power supply via 2 x 1.5 V battery AA size (not supplied)

There are restrictions or requirements within the EU!

Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!

## Technical data:

Multifrequency	: 1
General information	:
Description	: pocket transmitter
Carrier frequency range	: 1,785-1,800 MHz
Audio frequency range	: 60-16,000 Hz
Channels	: 1
THD	: -
Dynamic range	: -
Latency	:
RF S/N ratio	: -
Operating time	: ? 8 h
Admiss. ambient temp.	: 0-40 °C
Power supply	: -
Dimensions	: -
Total weight	: -
Connections	: -
Specifications transmitter	:
Transmitting power	: 10 mW
Operating range	: -
Power supply transmitter	: 2 x 1.5 V batt. AA size
Width transmitter	: 64 mm
Height transmitter	: 102 mm
Depth transmitter	: 28 mm
Weight transmitter	: 118 g
Connections transmitter	: 1 x 3-pole mini XLR
Specifications receiver	: -
Audio signal receiver	: -
Power supply receiver	: -
Width receiver	: -
Height receiver	: -
Depth receiver	: -
Weight receiver	: -
Connections receiver	: -