


PAS-254D - Procession Set



Portable amplifier system,
for processions and other mobile applications.

- Very comfortable to wear and great mobility due to backpack method
- 1 speaker with 4 speaker chassis
- Class D power amplifier
- Integrated 2-channel multifrequency wireless receiver (TXA-1822MR)
- Bluetooth receiver for wireless connection of mobile audio devices
- Adjustable USB/SD card player with connection for external storage media
- Built-in rechargeable lead gel battery 12 V/7.2 Ah (operating time: up to 7 hours)
- Compartment for spare rechargeable battery to extend operating time
- Integrated automatic battery charging
- Charging socket for supplied charger
- 1 input via comb. jack mic (XLR)/line (6.3 mm), gain control, tone control, mic input with 12 V phantom power
- 1 stereo line input via RCA jacks, gain control, tone control
- MIX OUT output (RCA)
- Output for a speaker (min. impedance: 4 Ohm), either additionally or alternatively to existing speakers
- Adjustable voice over function
- Limiter function
- Nylon backpack with storage pockets



Matching microphone transmitters or pocket transmitters are available at option, e.g. TXA-800HT and TXA-800HSE.

Licence-free in the EU.

Technical data:

Bluetooth	: 1
Multifrequency	: 1
Rated power (P_{RMS})	: 70 W
Peak output power	: 80 W
Frequency range	: 80-20,000 Hz
Carrier frequency	: 863.1-864.9 MHz
Operating range	: $\hat{\%}^{\wedge}$ 100 m
Inputs	: 2 $\hat{\text{A}}$ mV (mic), 14 mV (line, jack), 80 mV (line, RCA)

Link	: 300 mV
THD	: -
Max. SPL	: -
Equalizer, bass	: -
Equalizer, midrange	: -
Equalizer, treble	: -
Power supply	: rech. batt. 12 $\hat{\text{A}}$ V/7.2 $\hat{\text{A}}$ Ah
Admiss. ambient temp.	: 0-40 $^{\circ}$ C
Dimensions	: Total length: 120 $\hat{\text{A}}$ cm
Weight	: 7.7 kg
Connections	: 1 x XLR (mic), 1 x 6.3 mm jack (line), 1 x RCA L/R (line in), 1 x RCA L/R (line out), 1 x USB, 1 x SPEAKER