

ESP-134/WS - PA Wall Speaker

100V **4Ω** **new**



These wall speakers impress by an extraordinarily flat design which is only achieved by applying the latest NEODYMIUM magnetic systems.

The ESP-130... speaker systems already provide a very pleasant and complete sound and yet, with a total depth of only 38 mm, they are of such a flat design, that they are just as unobtrusive on the wall as a flush-mount speaker.

PA wall speaker

- 100 V line technique via audio transformer with 3 W and 6 W power taps or 4 Ohm operation (20 W)
- 2-way system with neodymium bass-midrange speaker and dome tweeter
- White plastic cabinet with protective metal grille
- Slimline design for unobtrusive wall mounting

Technical data:

100 V	: 1
Low-impedance	: 1
Active/passive	: passive
Transmission technology	: 100 V or low-impedance
Total output power	: -
Power rating (RMS)	: 6/3 W (100 V) 20 W (4 Ohm)
Total power rating	: -
Power rating (RMS)	: 6/3 W
Impedance	: 4 Ohm
Frequency range	: 80-18,000 Hz
THD	: -
S/N ratio	: -
Input signal	: -
System	: 2-way
Full range speaker	: -
Bass speaker	: -
Midrange speaker	: -
Tweeter	: -
Number of speakers	: 2
Speaker size	: 130
SPL	: 91 dB/W/m
Max. rated SPL	: 104 dB
Radiation angle/beam angle	: H: 100°/V: 60°
Radiation angle, horizontal	: 100°
Radiation angle, vertical	: 60°
Features	: -
Housing material	: plastic
Colour	: white
Mounting device	: attachment via screw
Protected against ball rebound	: -
Protection class	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: -
Dimensions	: 185 x 275 x 38 mm
Width	: 185 mm

Height	: 275 mm
Depth	: 38 mm
Weight	: 1.25 kg
Inputs	: spring-loaded terminal
Outputs	: -
Replacement voice coil	: -
Other features	: -
Accessories	: -
Packing dimensions (W x H x L)	: 0.075 x 0.225 x 0.315 m
Gross weight	: 1.375 kg
Net weight	: 1.255 kg