

## ESP-152/WS - PA Wall Speaker

100V



PA wall speaker

- 100 V line technique via audio transformer with 3 power taps
- High-quality sound and high volume capability due to 2-way coaxial system
- Plastic cabinet of a special design (open rear panel) with protective metal grille
- Symmetrical design allows for horizontal and vertical mounting
- Supplied with mounting screws and cover plates for the screws

## Technical data:

100 V	: 1
Active/passive	: passive
Transmission technology	: 100 V
Total output power	: -
Power rating (RMS)	: -
Total power rating	: -
Power rating (RMS)	: 15/7.5/3.75 W
Impedance	: -
Frequency range	: 100-20,000 Hz
THD	: -
S/N ratio	: -
Input signal	: -
System	: -
Full range speaker	: -
Bass speaker	: -
Midrange speaker	: -
Tweeter	: -
Number of speakers	: -
Speaker size	: 13 cm
SPL	: 91 dB/W/m
Max. rated SPL	: -
Radiation angle/beam angle	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Features	: -
Housing material	: plastic
Colour	: white
Mounting device	: -
Protected against ball rebound	: -
Protection class	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: -
Dimensions	: 240 x 330 x 85 mm
Width	: 240 mm
Height	: 330 mm

Depth	: 85 mm
Weight	: 1.84 kg
Inputs	: -
Outputs	: -
Replacement voice coil	: -
Other features	: -
Accessories	: -
Packing dimensions (W x H x L)	: 0.345 x 0.1 x 0.25 m
Gross weight	: 2.12 kg
Net weight	: 1.849 kg