
-

Technical data:

Outdoors	: 1
weatherproof	: 1
100 V	: 1
Low-impedance	: 1
protected against ball rebound	: 1
Active/passive	: passive
Transmission technology	: 100 V
Total output power	: -
Power rating (RMS)	: -
Total power rating	: 180 W
Power rating (RMS)	: 100/50/25 W
Impedance	: 8 Ohm
Frequency range	: 42-19,000 Hz
THD	: -
S/N ratio	: -
Input signal	: -
System	: 2-way bass-reflex
Full range speaker	: -
Bass speaker	: 16 cm bass speaker
Midrange speaker	: -
Tweeter	: 30 mm dome
Number of speakers	: 2
Speaker size	: 16 cm
SPL	: 90 dB/W/m
Max. rated SPL	: 110 dB
Radiation angle/beam angle	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Features	: -
Housing material	: ABS plastic
Colour	: white
Mounting device	: mounting bracket
Protected against ball rebound	: yes
Protection class	: IP45
Admiss. ambient temp.	: -30 °C to +40 °C

Power supply	: -
Dimensions	: 200 x 370 x 240 mm
Width	: 200 mm
Height	: 370 mm
Depth	: 240 mm
Weight	: 7.1 kg
Inputs	: screw terminal
Outputs	: -
Replacement voice coil	: -
Other features	: -
Accessories	: -
Packing dimensions (W x H x L)	: 0.31 x 0.47 x 0.24 m
Gross weight	: 8.42 kg
Net weight	: 7.68 kg