-

## Technical data:

| | | |
|---|---|---|
| Outdoors | : | 1 |
| weatherproof | : | 1 |
| 100 V | : | 1 |
| Low-impedance | : | 1 |
| protected against ball rebound | : | 1 |
| Active/passive | : | passive |
| Transmission technology | : | 100 V |
| Total output power | : | - |
| Power rating (RMS) | : | - |
| Total power rating | : | 240 W |
| Power rating (RMS) | : | 120/60/30Â W |
| Impedance | : | 8 Ohm |
| Frequency range | : | 50-20,000 Hz |
| THD | : | - |
| S/N ratio | : | - |
| Input signal | : | - |
| System | : | 2-way coaxial |
| Full range speaker | : | - |
| Bass speaker | : | 20 cm (8") PA coaxial |
| Midrange speaker | : | - |
| Tweeter | : | 25 mm (1") horn tweeter |
| Number of speakers | : | 2 |
| Speaker size | : | 20 cm (8") |
| SPL | : | 96 dB/W/m |
| Max. rated SPL | : | 117 dB |
| Radiation angle/beam angle | : | - |
| Radiation angle, horizontal | : | - |
| Radiation angle, vertical | : | - |
| Features | : | - |
| Housing material | : | ABS |
| Colour | : | white |
| Mounting device | : | mounting bracket |
| Protected against ball rebound | : | - |
| Protection class | : | IP45 |
| Admiss. ambient temp. | : | -30 °C to +40 °C |

| | |
|---|---|
| Power supply | : - |
| Dimensions | : 280 x 280 x 270Â mm |
| Width | : 280 mm |
| Height | : 280 mm |
| Depth | : 270 mm |
| Weight | : 9.5 kg |
| Inputs | : 1 x NEUTRIK SPEAKON, screw terminal |
| Outputs | : 1 x NEUTRIK SPEAKON, par. out |
| Replacement voice coil | : - |
| Other features | : - |
| Accessories | : - |
| Packing dimensions (W x H x L) | : 0.33 x 0.37 x 0.33 m |
| Gross weight | : 11.64 kg |
| Net weight | : 10.76 kg |