

## PAB-52WP/WS - PA Speaker Cabinet



**Vejrbestandig PA højttalere med IP-klassifikation.** Det rette valg, når der er brug for højttalere med høj lyd kvalitet og høj effekt, som kan tåle al slags vejr. Ideelle til permanent brug i det fri, fx i forlystelsesparker, i gågader, ved sportsarrangementer og andre steder, hvor det ikke er muligt at beskytte højttalerne mod vind og vejr. **Vejrbestandigt PA højttalersystem med høj effekt, 50 W**

- Kompakt bredtonet basreflekssystem i ABS-kabinet
- 100 V eller 4 Ohm drift
- 13 cm (5") full range højttaler i høj kvalitet med aluminiumsmembran
- Fremragende lydegenskaber
- Frontgitter med vandafvisende beklædning
- Forsænket terminal med dækplade og robust kabelforskrining
- Metaldele og vægbeslag af rustfrit stål
- Testet og godkendt som boldskudssikre iht. DIN 18032, part 3

### PROSOUND 05/2011

"The cabinets give a solid impression ... and meet IP45 requirements. All four speaker systems are suitable for pleasant background music ... the large PAB-8WP/WS is capable of quite high volume levels ... however, the small ones should not be underestimated ... these speaker systems are impressive and the price is quite reasonable for weatherproof speaker systems."

## Technical data:

Outdoors	: 1
weatherproof	: 1
100 V	: 1
Low-impedance	: 1
protected against ball rebound	: 1
Active/passive	: passive
Transmission technology	: 100 V
Total output power	: -
Power rating (RMS)	: -
Total power rating	: -
Power rating (RMS)	: 50/25/12.5 W
Impedance	: 4 Ohm
Frequency range	: 60-18,000 Hz
THD	: -
S/N ratio	: -
Input signal	: -
System	: wideband bass-reflex
Full range speaker	: 13 cm (5") full range speaker
Bass speaker	: -
Midrange speaker	: -
Tweeter	: -
Number of speakers	: 1
Speaker size	: 13 cm (5")
SPL	: 87 dB/W/m
Max. rated SPL	: 104 dB
Radiation angle/beam angle	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Features	: -
Housing material	: ABS
Colour	: white
Mounting device	: mounting bracket
Protected against ball rebound	: yes
Protection class	: IP45
Admiss. ambient temp.	: -10 °C to +40 °C

Power supply	: -
Dimensions	: 200 x 200 x 190 mm
Width	: 200 mm
Height	: 200 mm
Depth	: 190 mm
Weight	: 5.1 kg
Inputs	: screw terminal
Outputs	: -
Replacement voice coil	: -
Other features	: -
Accessories	: -
Packing dimensions (W x H x L)	: 0.25 x 0.29 x 0.23 m
Gross weight	: 6 kg
Net weight	: 5.46 kg